

HOW TO ORDER

# STYLE SA PRODUCT NUMBERS

Below Is An Example Of Building A Part Number For Ordering A Strainer

Size	Pressure Class	End Conn.	Strainer Type		Body Material	Perf Or Mesh	Screen Type	Screen Material		Gasket Type	Cover Conn.	Origin		Style
6	5	RF	Y	-	CS	062	P	34	-	G	B	B	-	SA

Description: 6" 600 lb. Flanged Y-Strainer, Carbon Steel Body, 1/16" Perforated 304ss screen, Spiral Wound 304ss Gasket – Graphite Filler, Bolted Cover, Domestic (Buy American), SA.

Size

--

Pressure Class

Ordering Number	ASME Pressure Class
5	600 Lb.
6	900 Lb.
7	1500 Lb.
8	2500 Lb.

End Connection

Ordering Number	End Connection
RF	Raised Face Flange
B8	Butt Weld, Sch 80/80S

Strainer Type

Ordering Number	Strainer Type
Y	Y-Pattern

Body Material

Ordering Number	Body Material
CS	Carbon Steel (ASTM A 216, Grade WCB)
FS	Forged Carbon Steel (ASTM A 105)

Perf or Mesh

Ordering Number	Perf. or Mesh
033	1/32"
045	3/64"
062	1/16"
094	3/32"
125	1/8"
156	5/32"
188	3/16"
250	1/4"
375	3/8"
500	1/2"
750	3/4"
M20	20 Mesh
M30	30 Mesh
M40	40 Mesh
M50	50 Mesh
M60	60 Mesh
M80	80 Mesh
M100	100 Mesh
M150	150 Mesh
M200	200 Mesh
M300	300 Mesh
X	Special

Screen Type

Ordering Number	Screen Type
P	Perforated
M	Mesh
L*	Perforated with Mesh Lining
S	Perforated with Mesh Lined Start Up
X	Special

\*20 mesh and finer screens must be reinforced with perforated screen.

Screen Material

Ordering Number	Screen Material
34	Type 304 Stainless Steel
36	Type 316 Stainless Steel
BR	Brass
ML	Monel
TI	Titanium
HC	Hastelloy C276
DS	Duplex Stainless Steel
X	Special

Gasket Type

Ordering Number	Gasket Type
G	Spiral Wound SS (304) – Graphite Filler
T	Spiral Wound SS (316) – Teflon Filler
S	Spiral Wound SS (316) – Graphite Filler
M	Spiral Wound Monel – Graphite Filler
X	Special

Cover Connection

Ordering Number	Cover Connection
B	Bolted

Origin

Country Code	Origin
B	Domestic (Buy American)
I	Import